

EMBE Chemical Resistance Chart

Testing in Accordance with ASTM 1308 Spot Test Procedures.

EMBE is resistant to the following reagents:

Automotive Fluids	Inorganic Salts
Grease	Calcium Chloride 20%
Motor Oil	Ammonium Chloride 20%
Transmission Oil	Sodium Chloride 20%
Anti-Freeze	Sodium Carbonate 20%
Gasoline	Sodium Phosphate 20%
Heptane	Sodium Sulfate 20%
Hexane	Magnesium Sulfate 20%
Solvents	Organic Acids
Acetone	Acetic 10%
Methalethyl Ketone	Citric 20%
Alcohol (Denatured)	Lactic 40%
Butyl Alcohol	Glueconic 40%
Butyl Acetate	Tartaric 40%
Carbon Tetrachloride	
Trichloroethylene	
Cellosolve Solvent	
Toluene	
Xylene	
Mineral Spirits	
Miscellaneous Chemicals	Inorganic Acids
Formaldehyde 20%	Chromic 20%
Hydrogen Peroxide 10%	Hydrochloric 30%
Javex	Nitric 40%
Window Cleaner	Sulphuric 60%
Vegetable Oil	Hydroflouric Acid 20%
	Phosphoric Acid 50%
Alkalis	
Ammonium Hydroxide (Conc)	
Potassium Hydroxide 30%	
Sodium Hydroxide 30%	
Sodium Silicate 20%	
Lime Water – Saturated Calcium – Hydroxide Solution	

Safety Precautions

Please refer to MSDS sheet